



图例:

- 1 吸气截止阀 Ø54.1 (2 1/8")
- 2 低压接头 1/4" SAE-FLARE
- 3 能量调节电磁阀
- 4 液体接口 Ø10 (选配)
- 5 经济器接口 Ø22 (选配)
- 6 高压接头 1/4" SAE-FLARE
- 7 排气截止阀 Ø42.2 (1-5/8")
- 8 油路接口 5/8" SAE-FLARE
- 9 低压侧放油口
- 10 接线盒
- 11 电磁阀接口 (无级能量控制)
- 12 油压接头 1/4" SAE-FLARE
- 13 排温传感器 1/8" NPT

Key:

- 1 Suction shut off valve Ø54.1 (2 1/8")
- 2 Low pressure gas 1/4" SAE-FLARE
- 3 Solenoid valves for part load operation
- 4 Liquid injection Ø10 (optional)
- 5 economizer Ø22 (optional)
- 6 High pressure gas 1/4" SAE-FLARE
- 6 Non return valve
- 7 Discharge shut-off valve Ø42.2 (1-5/8")
- 8 Oil Inlet Connection 5/8" SAE-FLARE
- 9 Oil drain motor housing
- 10 Electrical box
- 11 Solenoid valve connection (ILZ)
- 12 Oil pressure 1/4" SAE-FLARE
- 13 Oil temperature sensor 1/8" NPT