



图例:

- 1-喷嘴接头Ø10(选配)
- 2-排气温度传感器1/8"NPT
- 3-高压接头1/4"SAE-FLARE
- 4-能量调节电磁阀
- 5-低压接头1/4"SAE-FLARE
- 6-低压侧放油口
- 7-油压接头1/4"SAE-FLARE
- 8-油路接头5/8"SAE FLARE
- 9-排气截止阀 Ø54 (2-1/8")
- 10-单向阀
- 11-电磁阀板 (有级-无级转换)
- 12-接线盒
- 13-吸气截止阀 Ø80 (3-1/8")

Key:

- 1-Liquid injection connection $\Phi 10$
- 2-Economizer connection $\Phi 22$ (option)
- 2-011 temperature sensor 1/8"NPT
- 3-High pressure connection 1/4"SAE-FLARE
- 4 Solenoid valves for part load operation
- 5-Low pressure connection 1/4"SAE-FLARE
- 6 Oil drain port on low pressure
- 7-Oil pressure connection 1/4"SAE-FLARE
- 8 Oil inlet connection 5/8"SAE FLARE
- 9-Discharge shut-off valve Ø54 (2-1/8")
- 10-Check valve
- 11-Solenoid valve connection (L4-LZ)
- 12-Electrical box
- 13-Suction shut-off valve Ø80 (3-1/8")