

Модель	Номинальная мощность (Л.С)	Ном. об. производит ельность (м ³ /ч)	Патрубок всасывания	Патрубок нагнетания	Кол-во масла (Л)	Масса нетто (кг)	Питание двигателя компрессора	Макс. рабочий ток (А) (R404A)	Ток блокировки ротора (А)
HR36KC/E-PFJ	3	8.6	7/8	1/2	1.4	30	220~240V/50Hz	19.6	76
HR48KC/E-PFJ	4	11.4	7/8	1/2	1.4	37	220~240V/50Hz	24.5	114
HR61KC/E-PFJ	5	14.4	7/8	1/2	1.8	41	220~240V/50Hz	31.2	150
HR36KC/E-TFD	3	8.6	7/8	1/2	1.4	30	380~420V/50Hz	7.7	46
HR48KC/E-TFD	4	11.4	7/8	1/2	1.4	37	380~420V/50Hz	9.7	61
HR61KC/E-TFD	5	14.4	7/8	1/2	1.8	41	380~420V/50Hz	11.7	61
HR72KC/E-TFD	6	17.2	7/8	1/2	1.8	44	380~420V/50Hz	13.9	66
HR81KC/E-TFD	7	18.8	7/8	1/2	1.8	44	380~420V/50Hz	16.3	110
HR94KC/E-TFD	8	22.1	1-3/8	7/8	2.7	60	380~420V/50Hz	17.5	117
HR125KC/E-TFD	10	29.1	1-3/8	7/8	3	65	380~420V/50Hz	22.5	122
HR144KC/E-TFD	12	33.2	1-3/8	7/8	3	65	380~420V/50Hz	25.3	122
HR160KC/E-TFD	13	36.3	1-3/8	7/8	3.2	65	380~420V/50Hz	27.8	149
HR190KC/E-TFD	15	43.3	1-3/8	7/8	3.2	66	380~420V/50Hz	31.4	149

Модель	Q/P (W)	Температура конденсации, °C	Температура кипения						
			-20	-15	-10	-5	0	5	10
HR36KC/E-PFJ	Q/P	45	3272	3924	4931	6083	7247	8720	10457
HR48KC/E-PFJ	Q/P		4469	5360	6735	8310	9900	11912	14284
HR61KC/E-PFJ	Q/P		5518	6619	8316	10260	12224	14707	17638
HR36KC/E-TFD	Q/P		3272	3924	4931	6083	7247	8720	10457
HR48KC/E-TFD	Q/P		4469	5360	6735	8310	9900	11912	14284
HR61KC/E-TFD	Q/P		5518	6619	8316	10260	12224	14707	17638
HR72KC/E-TFD	Q/P		6644	7968	10012	12352	14716	17706	21234
HR81KC/E-TFD	Q/P		6984	8861	11018	13488	16308	19514	23141
HR94KC/E-TFD	Q/P		9016	10964	13623	16792	20307	24254	28226
HR125KC/E-TFD	Q/P		11896	14465	17973	22155	26791	31999	37240
HR144KC/E-TFD	Q/P		13369	16256	20199	24897	30109	35960	41850
HR160KC/E-TFD	Q/P		14606	17760	22067	27200	32894	39287	45722
HR190KC/E-TFD	Q/P		17425	21187	26327	32452	39244	46871	54548

Данные производительности рассчитаны при перегреве 11.1 К и переохлаждении 8.3 К